

Riverside, MO 64150 Telephone: 816,231,5580 Fax: 816,231,5641 www.occutec.com

March 26, 2019

Diane Czarnecki
Industrial Hygienist
Facilities Management Division
GSA Public Buildings Service - Heartland Region
2300 Main Street, Kansas City, MO 64108

RE: Goodfellow Federal Center – Bldg. # 102E Drinking Water Sampling Project # 918004.002

Dear Ms. Czarnecki:

Thank you for the opportunity to provide the General Services Administration (GSA) with the above referenced environmental sampling activities. The following is our report.

INTRODUCTION

As requested, OCCU-TEC conducted drinking water sampling and testing for the presence of lead and copper at Building #102E of the Goodfellow Federal Center located at 4300 Goodfellow Federal Boulevard in St. Louis, Missouri. Sampling was completed in response to the ongoing environmental condition assessment at the Goodfellow Federal Center which is documented at the Goodfellow Federal Center Reading Room located at https://www.gsa.gov/portal/content/212361.

Drinking water sampling was conducted to determine the current levels of lead and copper in representative sources throughout the complex. Drinking water sampling at Bldg. #102E was conducted on February 26, 2019 by Mr. Austin O'Byrne of OCCU-TEC.

METHODOLOGY

The sampling methodology used during this investigation was developed in general accordance with the United States Environmental Protection Agency's (EPA) "Quick Guide to Drinking Water Sample Collection – Second Edition" developed by the EPA Region 8 in September 2016.

Samples were collected as first draw samples in accordance with the Lead and Copper Rule (40 CFR Part 141 Subpart I). First draw samples represent 'worst case' conditions with water that has been stationary within the plumbing systems for a minimum of six hours. The samples were collected in individually labeled 1000 milliliter (mL) plastic bottles capped with Teflon septa lined screw caps. The bottles were filled to the shoulder with water from the sample source. The samples were then placed in a cooler for safe transport. Each sample was acidified at the laboratory as needed.

Drinking water sampling for the presence of lead and copper was conducted at four (4) distinct locations within Building #102E. A total of five (5) samples were obtained including a duplicate sample. After each drinking water sample was collected, OCCU-TEC filled a separate sample cup with approximately 2 inches of water. OCCU-TEC placed an Oakton model PHTester30 pH meter into the sample cup. After readings stabilized, OCCU-TEC recorded the readings for pH (the acidity or basicity of an aqueous solution) and the temperature (in degrees Celsius) on site specific sample logs.

Drinking water samples were submitted to Eurofins-Eaton Analytical in South Bend, IN for analyses of lead and copper. Eurofins-Eaton Analytical is certified by the State of Missouri Department of Natural Resources (MDNR) as an approved drinking water laboratory. Eurofins-Eaton Analytical's Missouri Certification number is 880.

The drinking water samples were collected using media supplied by Eurofins-Eaton Analytical. Lead and Copper samples were collected and analyzed in accordance with EPA Method 200.8.

RESULTS AND DISCUSSION

The results for the subject testing are summarized in the tables below.

Water Sample Summary

Analysis	Lowest Concentration	Highest Concentration	Action Level*
Lead	< 0.001 mg/L	< 0.001 mg/L	0.015 mg/L
Copper	0.025 mg/L	0.080 mg/L	1.3 mg/L

Samples with a "<" sign indicate that the results were below the reportable limit.

Specific water sample locations are indicated in Appendix A. A summary table of all sampling results by location is included in Appendix B. The complete laboratory report for the drinking water sampling from Eurofins-Eaton Analytical is attached in Appendix C.

^{*}As per EPA Lead and Copper Rule (40 CFR Part 141 Subpart I)

LEAD

All samples were below the Action Level (AL) for lead.

COPPER

All samples were below the AL for copper.

PH

Normal pH levels for drinking water are between 6.0 to 8.5. Water with a pH < 6.5 is considered acidic, soft, and corrosive. Acidic water may contain metal ions, may cause premature damage to metal piping, and increases the likelihood of leaching. Water with a pH > 8.5 is considered alkaline or basic and can indicate that the water is hard. Hard water does not pose a health risk but can cause aesthetic problems. These problems include an alkali taste, the formation of scale deposits, and difficulty in getting soaps and detergents to lather.

Recorded pH levels in Building #102E ranged from 8.92 to 9.33 indicating the drinking water is slightly alkaline.

LIMITATIONS

The scope of this assessment was limited in nature. OCCU-TEC collected samples from a select number of drinking water sources in an effort to minimize cost while providing a general overview of the drinking water quality at the site. Sample locations do not encompass every drinking water source at the Site. Additionally, samples were only analyzed for a select number of potential contaminants likely to affect the drinking water quality at the site. OCCU-TEC is not responsible for potential contaminants not identified in this report.

This report was prepared for the sole use of GSA. Reliance by any party other than GSA is expressly forbidden without OCCU-TEC's written permission. Any parties relying on the report, with OCCU-TEC's written permission, are bound by the terms and conditions outlined in the original proposal as if said proposal was prepared for them.

OCCU-TEC appreciates the opportunity to work with the General Services Administration on this project. Please contact us if you have any questions regarding this report or if we may be of any additional service.

Sincerely,



Jeff T. Smith Senior Project Manager (b) (6)

Kevin Heriford Project Manager (QA/QC)

ATTACHMENTS

Appendix A, Water Sample Location Diagrams Appendix B, Results Summary by Location Appendix C, Water Sample Laboratory Report

Appendix A Water Sample Location Diagrams

5 | P a g e

Building Floor Plans were not available for this building.

Appendix B Results Summary by Location

	Goodfellow Federal Center - Building 102E													
Sample Number	Location	Water Source	Temperature	рН	Analyte	Result	Units	Above/Below	AL					
	1st Floor Column L 21 - Left Side	Drinking Fountain	18.8	9.27	Copper	0.042	mg/L	Below AL	1.3					
GFC-102E-01	1st Floor Column L 21 - Left side	Drillking Fountain	10.0	9.27	Lead	< 0.001	mg/L	Below AL	0.015					
	1st Floor Column L 21 - Right Side	Drinking Fountain	18.3	9.19	Copper	0.025	mg/L	Below AL	1.3					
GFC-102E-02	13t Floor Column L 21 - Right Side	Dilliking Fountain	10.5	3.13	Lead	< 0.001	mg/L	Below AL	0.015					
	2nd Floor Column L 21	Drinking Fountain	18.4	8.92	Copper	0.026	mg/L	Below AL	1.3					
GFC-102E-03	ZHU FIOOI COIUITHI L ZI	Dilliking Fountain	10.4	0.32	Lead	< 0.001	mg/L	Below AL	0.015					
	1st Floor Column P 25	Sink	17.1	9.33	Copper	0.08	mg/L	Below AL	1.3					
GFC-102E-04	1st Floor Column F 25	SILIK	17.1	3.33	Lead	< 0.001	mg/L	Below AL	0.015					
	1st Floor Column P 25	Sink	17.1	9.33	Copper	0.077	mg/L	Below AL	1.3					
GFC-102E-04-DUP	13t Floor Column P 23	JIIK	17.1	9.33	Lead	< 0.001	mg/L	Below AL	0.015					

Highlight indicates results at or above the Action Level (AL)

Appendix C Water Sample Laboratory Report



LABORATORY REPORT

If you have any questions concerning this report, please do not hesitate to call us at (800) 332-4345 or (574) 233-4777.

This report may not be reproduced, except in full, without written approval from EEA.



STATE CERTIFICATION LIST

State	Certification	State	Certification		
Alabama	40700	Missouri	880		
Alaska	IN00035	Montana	CERT0026		
Arizona	AZ0432	Nebraska	NE-OS-05-04		
Arkansas	IN00035	Nevada	IN00035		
California	2920	New Hampshire*	2124		
Colorado	IN035	New Jersey*	IN598		
Colorado Radiochemistry	IN035	New Mexico	IN00035		
Connecticut	PH-0132	New York*	11398		
Delaware	IN035	North Carolina	18700		
Florida*	E87775	North Dakota	R-035		
Georgia	929	Ohio	87775		
Hawaii	IN035	Oklahoma	D9508		
Idaho	IN00035	Oregon (Primary AB)*	4074-001		
Illinois*	200001	Pennsylvania*	68-00466		
Illinois Microbiology	17767	Puerto Rico	IN00035		
Illinois Radiochemistry	IN00035	Rhode Island	LAO00343		
Indiana Chemistry	C-71-01	South Carolina	95005		
Indiana Microbiology	M-76-07	South Dakota	IN00035		
Iowa	098	Tennessee	TN02973		
Kansas*	E-10233	Texas*	T104704187-15-8		
Kentucky	90056	Texas/TCEQ	TX207		
Louisiana*	LA180008	Utah*	IN00035		
Maine	IN00035	Vermont	VT-8775		
Maryland	209	Virginia*	460275		
Massachusetts	M-IN035	Washington	C837		
Michigan	9926	West Virginia	9927 C		
Minnesota*	018-999-338	Wisconsin	999766900		
Mississippi	IN035	Wyoming	IN035		
EPA	IN00035				

*NELAP/TNI Recognized Accreditation Bodies

Revision date: 01/02/2018



110 South Hill Street South Bend, IN 46617 Tel: (574) 233-4777 Fax: (574) 233-8207

1 800 332 4345

Laboratory Report

Client: OCCU-TEC Inc. Report: 445055

Attn: Kevin Heriford Priority: Standard Written

100 NW Business Park Lane Status: Final

Riverside, MO 64150 PWS ID: Not Supplied

	Sample Information														
EEA ID#	Client ID	Method	Collected Date / Time	Collected By:	Received Date / Time										
4216180	GFC-102E-01	200.8	02/26/19 07:05	Client	03/05/19 09:00										
4216181	GFC-102E-02	200.8	02/26/19 07:09	Client	03/05/19 09:00										
4216182	GFC-102E-03	200.8	02/26/19 07:15	Client	03/05/19 09:00										
4216183	GFC-102E-04	200.8	02/28/19 05:42	Client	03/05/19 09:00										
4216184	GFC-102E-04 DUP	200.8	02/28/19 05:42	Client	03/05/19 09:00										

Report Summary

Detailed quantitative results are presented on the following pages. The results presented relate only to the samples provided for analysis.

We appreciate the opportunity to provide you with this analysis. If you have any questions concerning this report, please do not hesitate to call Kelly Blackburn at (574) 233-4777.

Note: This report may not be reproduced, except in full, without written approval from EEA.

(b) (6)

ASM

03/18/2019

Date

Authorized Signature
Client Name: OCCU-TEC Inc.

Report #: 445055

Title

Client Name: OCCU-TEC Inc. Report #: 445055

Sampling Point: GFC-102E-01 PWS ID: Not Supplied

Lead and Copper													
Analyte ID #	Analyte	Method Reg MRL† Result Limit		Units Preparation Analy Date		Analyzed	EEA ID#						
7440-50-8	Copper	200.8	1300 !	1.0	42	ug/L		03/14/19 14:46	4216180				
7439-92-1	Lead	200.8	200.8 15! 1.0 < 1.0		< 1.0	ug/L		03/14/19 14:46	4216180				

Sampling Point: GFC-102E-02 PWS ID: Not Supplied

			Le	ad and (Copper				
Analyte ID #	Analyte	Method	Method Reg MRL† Result Units				Preparation Date	Analyzed	EEA ID#
7440-50-8	Copper	200.8	1300 !	1.0	25	ug/L		03/14/19 14:48	4216181
7439-92-1	Lead	200.8	15 !	1.0	< 1.0	ug/L		03/14/19 14:48	4216181

Sampling Point: GFC-102E-03 PWS ID: Not Supplied

			Le	ad and (Copper				
Analyte ID #	Analyte	Method	Method Reg MRL† Result Units				Preparation Date	Analyzed	EEA ID#
7440-50-8	Copper	200.8	1300 !	1.0	26	ug/L		03/14/19 14:49	4216182
7439-92-1	Lead	200.8	15 !	1.0	< 1.0	ug/L		03/14/19 14:49	4216182

Sampling Point: GFC-102E-04 PWS ID: Not Supplied

	Lead and Copper														
Analyte ID #	Analyte	Method Reg MRL† Result		Units	Preparation Date	Analyzed	EEA ID#								
7440-50-8	Copper	200.8	1300 !	1.0	80	ug/L		03/14/19 14:51	4216183						
7439-92-1	Lead	200.8	200.8 15! 1.0 < 1.0		ug/L		03/14/19 14:51	4216183							

Sampling Point: GFC-102E-04 DUP PWS ID: Not Supplied

			Le	ad and (Copper				
Analyte ID #	Analyte	Method	Method Reg MRL† Result U				Preparation Date	Analyzed	EEA ID#
7440-50-8	Copper	200.8	1300 !	1.0	77	ug/L		03/14/19 14:53	4216184
7439-92-1	Lead	200.8	15 !	1.0	< 1.0	ug/L		03/14/19 14:53	4216184

† EEA has demonstrated it can achieve these report limits in reagent water, but can not document them in all sample matrices.

Reg Limit Type:	MCL	SMCL	AL
Symbol:	*	۸	!

Client Name: OCCU-TEC Inc. Report #: 445055

Lab Definitions

Continuing Calibration Check Standard (CCC) / Continuing Calibration Verification (CCV) / Initial Calibration Verification Standard (ICV) / Initial Performance Check (IPC) - is a standard containing one or more of the target analytes that is prepared from the same standards used to calibrate the instrument. This standard is used to verify the calibration curve at the beginning of each analytical sequence, and may also be analyzed throughout and at the end of the sequence. The concentration of continuing standards may be varied, when prescribed by the reference method, so that the range of the calibration curve is verified on a regular basis. CCL, CCM, and CCH are the CCC standards at low, mid, and high concentration levels, respectively.

Internal Standards (IS) - are pure compounds with properties similar to the analytes of interest, which are added to field samples or extracts, calibration standards, and quality control standards at a known concentration. They are used to measure the relative responses of the analytes of interest and surrogates in the sample, calibration standard or quality control standard.

Laboratory Duplicate (LD) - is a field sample aliquot taken from the same sample container in the laboratory and analyzed separately using identical procedures. Analysis of laboratory duplicates provides a measure of the precision of the laboratory procedures.

Laboratory Fortified Blank (LFB) / Laboratory Control Sample (LCS) - is an aliquot of reagent water to which known concentrations of the analytes of interest are added. The LFB is analyzed exactly the same as the field samples. LFBs are used to determine whether the method is in control. FBL, FBM, and FBH are the LFB samples at low, mid, and high concentration levels, respectively.

Laboratory Method Blank (LMB) / **Laboratory Reagent Blank (LRB)** - is a sample of reagent water included in the sample batch analyzed in the same way as the associated field samples. The LMB is used to determine if method analytes or other background contamination have been introduced during the preparation or analytical procedure. The LMB is analyzed exactly the same as the field samples.

Laboratory Trip Blank (LTB) / **Field Reagent Blank (FRB)** - is a sample of laboratory reagent water placed in a sample container in the laboratory and treated as a field sample, including storage, preservation, and all analytical procedures. The FRB/LTB container follows the collection bottles to and from the collection site, but the FRB/LTB is not opened at any time during the trip. The FRB/LTB is primarily a travel blank used to verify that the samples were not contaminated during shipment.

Matrix Spike Duplicate Sample (MSD) / Laboratory Fortified Sample Matrix Duplicate (LFSMD) - is a sample aliquot taken from the same field sample source as the Matrix Spike Sample to which known quantities of the analytes of interest are added in the laboratory. The MSD is analyzed exactly the same as the field samples. Analysis of the MSD provides a measure of the precision of the laboratory procedures in a specific matrix. SDL, SDM, and SDH / LFSMDL, LFSMDM, and LFSMDH are the MSD or LFSMD at low, mid, and high concentration levels, respectively.

Matrix Spike Sample (MS) / Laboratory Fortified Sample Matrix (LFSM) - is a sample aliquot taken from field sample source to which known quantities of the analytes of interest are added in the laboratory. The MS is analyzed exactly the same as the field samples. The purpose is to demonstrate recovery of the analytes from a sample matrix to determine if the specific matrix contributes bias to the analytical results. MSL, MSM, and MSH / LFSML, LFSMM, and LFSMH are the MS or LFSM at low, mid, and high concentration levels, respectively.

Quality Control Standard (QCS) / Second Source Calibration Verification (SSCV) - is a solution containing known concentrations of the analytes of interest prepared from a source different from the source of the calibration standards. The solution is obtained from a second manufacturer or lot if the lot can be demonstrated by the manufacturer as prepared independently from other lots. The QCS sample is analyzed using the same procedures as field samples. The QCS is used as a check on the calibration standards used in the method on a routine basis.

Reporting Limit Check (RLC) / Initial Calibration Check Standard (ICCS) - is a procedural standard that is analyzed each day to evaluate instrument performance at or below the minimum reporting limit (MRL).

Surrogate Standard (SS) / **Surrogate Analyte (SUR)** - is a pure compound with properties similar to the analytes of interest, which is highly unlikely to be found in any field sample, that is added to the field samples, calibration standards, blanks and quality control standards before sample preparation. The SS is used to evaluate the efficiency of the sample preparation process.



Eaton Analytical

110 S. Hill Street South Bend, IN 46617 T: 1.800.332.4345 F: 1.574.233.8207

w	ww.EurofinsUS.com/Eaton	for EEA us	a amb.			CHA	AIN OF	CUSTODY RI	ECORI	D	A COLUMN TO SERVICE STREET, SE	Page	_ }	of	7	_
R	Shaded area EPORT TO: JARNOU 800	CUTEC.	C. DIAA			SAMPLER (Signature)		PWS ID#		STATE (sample origin)	PROJECT NAME	<u> </u>	O#			
	DO NW Business F					b) (6)	-	FWS ID#		CITTL (Sample Origin)		100	SCALE			
6	2: Jurside, MO G							AU		Mo	Goodfellow Federal Center	9180	04.			
B	ILL TO: OCCU-TEC					// Yes	No	POPULATION SER	RVED	SOURCE WATER	feucral	002	116	SS		Ĭ N
10	oo NW Business	Park las	2		ļ	/ COMPLIANCE	,				Center	2.5		Ä	ш	TO
1	Riverside, MO	CUISA				MONITORING	X	NA	0	Nuncipal				IA	OD	S
-	LAB Number		OLLECTION	J					FEGT MANAGE			CHLOR	RINATED	CONTAINERS	MATRIX CODE	TURNAROUND TIME
1		DATE	TIME	AM	PM	SAMPLING SITE		1	TEST NAME	=	SAMPLE REMARKS	YES		P	IAT	U.R.
	4126180	2-24-19	7:05	X	-	10 GFC-102E-01		Lead + Co	opper			×	INO	#	DW	COMPAND OF STREET
	1 161	2-64-19	7:09	X		GFC-107E- 07			oper			×			PW PW	SW
3	165	2-24-19	7:15	X		GFC-1021= -03			pper			X			DW	SW
	183	2-28-19		X		GFC-102F= -04			pper			X		1	OW	32
	Cil	7-28-19	5:42	X		GFC-102E - 04DUP			pper			X		i	OW	
(oper			-		•	UW	200
7								1	nner							
8									pper							
9									pper							
1									pper							
1									pper					_		
1	-								pper							
1						(m - 1		lead + Co.								
1								Lead + Cop	200.0							
									MO.							
	ELINOUISHED RY-(Signature D) (6))	DATE	TIM	- 1	RECEIVED BY:(Signature)	DATE			THE RIGHT TO RETURN UNU	ISED PORTIONS OF NON-A	QUEOUS	SAMPLES TO	CLIENT		
1	3) (0)		3-1-19	1:30				LAB COMME	ENTS							
Į				AM C				AM PM								
	1/		DATE	TIM	E	RECEIVED BY:(Signature)	DATE	TIME								
	V			1												
				AM				AM PM	*******	***************************************		-		-		
R	ELINQUISHED BY:(Signature)	DATE	TIM	E	RECEIVED FOR LABORATORY BY:	DATE	TIME	S UPON RECE	EIPT (check one):						
				-		(b) (6)	101	0904	Iced: Wet/BI	lue Ambient	°C Upon F	Receipt	×	N/A		
				AM !			1-100	AM PM				toootpt _				
	MATRIX CODES:		TURN-ARC	ד מאטכ	TME	(TAT) - SURCHARGES										
	DW-DRINKING WATER RW-REAGENT WATER		SW = Standar		n X a Consider	PACAGO CONTRACTOR OF TABLE ACCUSOCIO		e Verbal: (3 working days)	100%							
D	GW-GROUND WATER EW-EXPOSURE WATER		RV* = Rush Ve		7			e Written: (3 working days)	125%		Samples received unant than 48 hours holding ti					
Page	SW-SURFACE WATER			WORKIT	ng days) 75%	SF* = Weeken STAT* = Less	8 85	CALL		be subject to additional		iy illay				
6 of	MANAGET WATER			lited	service not available for all testing	- Less	10 110uis	UPILL						200 march		
	ample analysis will be provided a	ccording to the				rvices Terms, which are available upon request.	Any other te	rms proposed by Custome	er are deeme		06-LO-F0435 Issue 7					a by